



SPIN

Automatic stretch wrappers that can wrap palletized loads in lines of heavy production and have been designed to turn their columns to maintain load stability. They are designed to be integrated into production lines without any manual intervention being required. These machines are completely customizable with a wide range of options and accessories that facilitate the perfect solution for your production requirements and work environment.

WRAPPER SPIN

PERFORMANCE

Output	60 pallets/hours
Pallet Maximum Sizes	1200 x 1200 mm
Load Maximum Height	2400 mm
Load Maximum Weight	2000 kg

MAIN FEATURES

Film Tension Control	Powered Pre-stretching
Film Cutting	Thermal Blade
Hotwelding on load	Included
Pre-stretching Relation	100 - 150 -250%
Platform Turning Speed Control	✓
Reel Carriage Speed Control	✓
Film Maximum Width	500 mm
Film Capacity (Reel Diameter)	260 mm

PLATAFORMA

Turning Device	Rotating arm
Turning Speed	30 RPM
Height	500 mm
Conveyor Width	940/1340 mm

WEIGHT & SIZES

Weight	2000 kg	
Sizes	L	3990 mm
	W	3390 mm
	H	3680 mm

UTILITIES

Pneumatics	6 bar
Consumption	120 l/cycle
Electrics	230/400V III+N+T
Consumption	4 kW/h

OPTIONS

Column Height	3400 mm
Load Maximum Weight	Max. 3000 kg
Powered Top Platen to stabilise load	✓
COVERMATIC Top Film Sheet Dispenser	✓
Blade Film Cutting	✓
Safety Fencing	✓
Film Stringer	✓
Raised Legs on Base	✓
Double Reel Support	-
Adaptation to different working environments and temperatures	✓
Stainless Steel version	✓
ANFID Tape Dispenser	-
RFID Label Reader	✓
Jumbo Reels	✓